SAFETY DATA SHEET

1. Identification

Product number 1000012747

Product identifier 11 OZ HI-P QUICK DRY LB 12PK
Company information ARMCHEM INTERNATIONAL CORP

3563 N.W. 53RD COURT

FT. LAUDERDALE, FL 33309 United States

Emergency telephone US
Emergency telephone outside

1-866-836-8855 1-952-852-4646

บร

Version # 09

Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Germ cell mutagenicityCategory 1B

Carcinogenicity Category 1B Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or

Category 2

repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Use only outdoors or in a well-ventilated area. Wear

protective gloves/protective clothing/eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or

concerned: Get medical advice/attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Not available.

Product #: 1000012747 Version #: 09 Issue date: 03-25-2015

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|------------|
| Naphtha (petroleum), hydrotreated light | | 64742-49-0 | 40 - 60 |
| 1,1-Difluoroethane | | 75-37-6 | 20 - 40 |
| n-Hexane | | 110-54-3 | 20 - 40 |
| Dead Record | | N/A | 2.5 - 10 |
| Cyclohexane | | 110-82-7 | 0.1 - 1 |
| Other components below reportable leve | els | | 0.01 - 0.1 |

^{#:} This substance has workplace exposure limit(s).

4. First-aid measures

Skin contact

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a

POISON CENTER or doctor/physician if you feel unwell. Call a physician or Poison Control Center immediately.

Call a physician or Poison Control Center immediately. Eve contact Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods

Powder. Foam. Carbon dioxide (CO2).

Do not use a solid water stream as it may scatter and spread fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

clothing will only provide limited protection.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

| Components | Туре | Value | |
|---------------------------------|---------------|------------|--|
| Cyclohexane (CAS 110-82-7) | PEL | 1050 mg/m3 | |
| | | 300 ppm | |
| Dead Record (CAS N/A) | PEL | 980 mg/m3 | |
| | | 400 ppm | |
| n-Hexane (CAS 110-54-3) | PEL | 1800 mg/m3 | |
| | | 500 ppm | |
| US. ACGIH Threshold Limit Value | s | | |
| Components | Туре | Value | |
| Cyclohexane (CAS 110-82-7) | TWA | 100 ppm | |
| Dead Record (CAS N/A) | STEL | 400 ppm | |
| | TWA | 200 ppm | |
| n-Hexane (CAS 110-54-3) | TWA | 50 ppm | |
| US. NIOSH: Pocket Guide to Cher | nical Hazards | | |
| Components | Туре | Value | |
| Cyclohexane (CAS 110-82-7) | TWA | 1050 mg/m3 | |
| | | 300 ppm | |
| Dead Record (CAS N/A) | STEL | 1225 mg/m3 | |
| | | 500 ppm | |
| | TWA | 980 mg/m3 | |
| | | 400 ppm | |
| n-Hexane (CAS 110-54-3) | TWA | 180 mg/m3 | |

Value Components Type 50 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Value **Type** TWA 1,1-Difluoroethane (CAS 2700 mg/m3 75-37-6)

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|-------------------------|----------|---|----------|---------------|
| Dead Record (CAS N/A) | 40 mg/l | Acetone | Urine | * |
| n-Hexane (CAS 110-54-3) | 0.4 mg/l | 2,5-Hexanedio n, without hydrolysis | Urine | * |

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

1000 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear tight-fitting goggles or face shield. Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of

an impervious apron is recommended. It may provide little or no thermal protection.

Skin protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes. Do not get this material in contact with skin. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear. **Appearance** Gas. Physical state Aerosol. Form Color Colorless. Solvent. Odor **Odor threshold** Not available. Not available. pН

Initial boiling point and boiling -12.46 °F (-24.7 °C) estimated

Melting point/freezing point

range

-58.0 °F (-50.0 °C) Propellant estimated Flash point

Not available.

Evaporation rate Not available.

Product #: 1000012747 Version #: 09 Issue date: 03-25-2015

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

3.9 % estimated

(%)

Flammability limit - upper

15.6 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 40 - 50 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 580.77 °F (304.87 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Specific gravity 0.673 - 0.693 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Acids. Strong oxidizing agents. Isocyanates. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation

may be harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat.

Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes and mucous

membranes. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product Species Test Results

11 OZ HI-P QUICK DRY LB 12PK (CAS Mixture)

Acute

Dermal

LD50 Rat 7082 mg/kg

Inhalation

LC50 Rat 806 mg/l/4h

Product name: 11 OZ HI-P QUICK DRY LB 12PK
Product #: 1000012747 Version #: 09 Issue date: 03-25-2015

| Components | Species | Test Results |
|----------------------------------|---|------------------------|
| 1,1-Difluoroethane (CAS 75-37-6 |) | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 44 - 437500 %, 4 Hours |
| Cyclohexane (CAS 110-82-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | _ | |
| LC50 | Rat | > 32880 mg/m3, 4 Hours |
| | | > 5540 ppm, 4 Hours |
| Dead Record (CAS N/A) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 16.4 ml/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | > 10000 ppm, 6 Hours |
| Oral | | |
| LD50 | Rat | 5.84 g/kg |
| Naphtha (petroleum), hydrotreate | ed light (CAS 64742-49-0) | |
| Acute | | |
| Dermal | | |
| LD50 | Guinea pig; Rabbit | > 9.4 ml/kg, 24 Hours |
| | Rabbit | > 1900 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | > 5020 mg/m3, 4 Hours |
| | | > 4980 mg/m3 |
| | | > 4980 mg/m3, 4 Hours |
| | | > 4.96 mg/l, 4 Hours |
| | | 13700 ppm, 4 Hours |
| Oral | | 10700 μμπ, 4 πομισ |
| <i>Oral</i> LD50 | Rat | 4820 mg/kg |
| n-Hexane (CAS 110-54-3) | Nat | 4020 Hig/kg |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg, 4 Hours |
| 2200 | . rabbit | > 5 ml/kg, 4 Hours |
| link alakia ia | | > 5 mi/kg, 4 modis |
| <i>Inhalation</i> LC50 | Rat | > 5000 ppm, 24 Hours |
| L000 | Nat | |
| | | > 31.86 mg/l |
| | | 73860 ppm, 4 Hours |
| Oral | 5 . | 04 15 |
| LD50 | Rat | 24 ml/kg |
| | | 24 g/kg |
| | Wistar rat | 49 g/kg |
| | be based on additional component data n | |

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Not available. Respiratory sensitization

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity repeated exposure

Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system. May cause

damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways. **Aspiration hazard**

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or **Chronic effects**

repeated exposure.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

| Product | | Species | Test Results |
|----------------------|----------------|-----------------------------------|-----------------------------------|
| 11 OZ HI-P QUICK DRY | Y LB 12PK (CAS | Mixture) | |
| Aquatic | | | |
| Algae | IC50 | Algae | 11111 mg/L, 72 Hours |
| Fish | LC50 | Fish | 10.2822 mg/L, 96 Hours |
| Components | | Species | Test Results |
| Cyclohexane (CAS 110 | -82-7) | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (Pimephales promel | las) 23.03 - 42.07 mg/l, 96 hours |
| Dead Record (CAS N/A |) | | |
| Aquatic | | | |
| Algae | IC50 | Algae | 1000.0001 mg/L, 72 Hours |
| Crustacea | EC50 | Daphnia | 13299 mg/L, 48 Hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 1400 mg/l, 96 hours |
| n-Hexane (CAS 110-54 | -3) | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (Pimephales promel | las) 2.101 - 2.981 mg/l, 96 hours |

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

0.75 1,1-Difluoroethane Cyclohexane 3.44 n-Hexane 3.9

No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Cyclohexane (CAS 110-82-7)

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

U056

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Waste from residues / unused

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1 Not applicable.

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 None Packaging non bulk Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

2.1 Class Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Environmental hazards Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed. **Packaging Exceptions** LTD QTY

IMDG

UN1950 **UN** number **UN proper shipping name AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

Environmental hazards

Marine pollutant Yes F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Product #: 1000012747 Version #: 09 Issue date: 03-25-2015

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexane (CAS 110-82-7) Listed. n-Hexane (CAS 110-54-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** Delayed Hazard - Yes

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. | |
|---------------|------------|------------|--|
| n-Hexane | 110-54-3 | 20 - 40 | |
| Cyclohexane | 110-82-7 | 0.1 - 1 | |
| Benzene | 71-43-2 | 0.01 - 0.1 | |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) n-Hexane (CAS 110-54-3)

US. New Jersey Worker and Community Right-to-Know Act

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) n-Hexane (CAS 110-54-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7) n-Hexane (CAS 110-54-3)

US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) n-Hexane (CAS 110-54-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Voc

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-25-2015

Version # 09

Disclaimer

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.